

WICANDERS

RE-VARNISHING

RE-VARNISHING

All Amorim Cork Flooring factory finished floors come with a wear layer and are ready for immediate use after installation. Therefore, no varnishing is required after installation. Only in very specific situations where spillages frequently occur or when extreme maintenance with water is required.

NOTE: Please use only recommended products by WICANDERS

cork Go

cork Essence

wood Essence

Varnishing & Re-Varnishing	Wicanders Power Contact + W 2000	Loba	LOBADUR WS 2K Contact + LOBADUR WS 2K Duo LOBADUR 2K Invisible Protect A.T.
		Bona	Bona Diamond Abrasive + Bona Traffic
		Eukula	Strato 461/462 With Hardener Strato 460
		Dr. Schutz	PU Sealer 100
		Mapei	Ultracoat High Traffic 10

Refurbishment

PS: We do not recommend the renovation of old floors if we do not know their history, especially the kind of maintenance products which have been used. If we know all about the maintenance products that were used and we can guarantee that they were completely removed, we can apply one coat of one as mentioned above.

When a floor needs refurbishing, you must remove all maintenance products, dirt, etc., with Wicanders Power strip.

Residues of maintenance products will cause lack of adhesion.

It is recommendable to make an adherence test between the old and new coat on a small area before the final varnishing.

Do not clean the floor with water or detergent for about two weeks after applying the varnish. After this period use Wicanders recommended maintenance products.

Amorim Cork Flooring S.A
(+351) 227 475 600

www.wicanders.com