

VARNISHING & RE-VARNISHING

GENERAL RULES

For varnishing we recommend a range of varnishes, which will give pleasant results.

For Glue-down floors, you should wait 24-36 hours after installation of the floor, to allow the flooring adhesive to dry completely.

NOTE: Please use only recommended products by Amorim WISE

Type of Surface	Varnishing
Cork Pure PU Finished*	Clean with a damp mop (clean water). After drying apply one or two coats recommended products by Amorim Wise below.
Cork Pure Sanded*	The floor must be varnished with minimum 3 coats of recommended products by Amorim Wise below. It is recommended that the floor is carefully sanded (screen pad # 220) to obtain a more uniform surface. Vacuum the floor very well. Follow the varnish producer recommendations Drying the first coating overnight (reduces risk of granule swelling) Intermediate sanding before the last application is recommended.

* for more information consult table below

RE-VARNISHING

All Amorim Cork Flooring factory finished floors come with a wear layer and are ready for immediate use after installation. Therefore, no varnishing is required after installation. Only in very specific situations where spillages frequently occur or when extreme maintenance with water is required.

AMORIM WISE HRT PRODUCTS

AMORIM WISE HRT PRODUCTS		
cork inspire 700 HRT	cork pure	
wood inspire 700 HRT	cork pure floor & wall	
	cork pure Signature	
	stone inspire 700 HRT	
	stone pure	
Varnishing & Re-Varnishing	Wicanders Power Contact + W 2000	Loba LOBADUR WS 2K Contact + LOBADUR WS 2K Duo LOBADUR 2K Invisible Protect A.T.
		Bona Bona Diamond Abrasive + Bona Traffic
		Eukula Strato 461/462 With Hardener Strato 460
		Dr. Schutz PU Sealer 100
		Mapei Ultracoat High Traffic 10
		Vermeister Abrasion # 220 + VERMEISTER IDRO 2K

Refurbishment

PS: We do not recommend the renovation of old floors if we do not know their history, especially the kind of maintenance products which have been used. If we know all about the maintenance products that were used and we can guarantee that they were completely removed, we can apply one coat of one as mentioned above.

When a floor needs refurbishing, you must remove all maintenance products, dirt, etc.

Residues of maintenance products will cause lack of adhesion.

It is recommendable to make an adherence test between the old and new coat on a small area before the final varnishing.

Do not clean the floor with water or detergent for about two weeks after applying the varnish. After this period use Amorim Wise recommended maintenance products.

Amorim Cork Flooring S.A
(+351) 227 475 600

www.amorimwise.com